

DIGITAL SENSOR

C4E : CONDUCTIVITY/SALINITY

Digital Technology for optimized measures

- 4 electrodes (2 graphic, 2 platinum)
- Range 0 to 200 mS/cm
- Digital sensor / **Modbus** RS-485
- Robust and Watertight




Applications :

- Urban wastewater treatment
- Industrial effluent treatment
- Surface water monitoring
- Sea water
- Drinking water

Mounting at 4 electrodes:

The electrode works with a technology in 4 electrodes: an alternating current of constant-voltage is established between a primary's pair of electrodes in graphite. The secondary's electrodes in platinum allow of regulate the voltage imposed to primary's electrodes to reflect of the fouling. The voltage measured between the primary's electrodes is in function of the resistance of place and so, of the conductivity.



SMART STORM LTD

WASTE WATER SOLUTIONS

C4E Specifications

Measure principle	Conductivity sensor with 4 electrodes (2 graphic, 2 platinum).
Measure ranges conductivity	0-200,0 μ S/cm 0 -2000 μ S/cm 0,00 -20,00 mS/cm 0,0 -200,0 mS/cm
Resolution	0,01 to 1 according the range
Accuracy	+/- 1 % of the full range
Measure range salinity	5-60 g/Kg
Measure range TDS -KCl	0-133 000 ppm
Response time	< 5 s
Working temperature	0°C to 50°C
Temperature compensation	CTN
Stocking temperature	- 10°C to + 60°C
Signal interface	Modbus RS-485 (option SDI-12)
Maximum refreshing time	Max < 1 s
Sensor power-supply	5 to 12 volts
Power Consumption	Standby : 25 μ A Average RS485 (1 measure/seconde) : 6,3 mA Current pulse : 500 mA
Sensor	
Dimensions	Diameter : 27 mm ; Lenght : 177 mm
Weight	350g (sensor + 3 m cable)
Material	PVC, stainless steel
Maximum pressure	5 bars
Connection	9 armoured connectors, polyurethane jacket, bare-wires or waterproof Fisher connector
Protection	IP68

<i>Dimensions</i>	<i>Wiring diagram</i>																			
	<p>Cable length up to 15m</p> <table border="1"> <tr><td>1</td><td>Power supply V+</td></tr> <tr><td>2</td><td>SDI-12</td></tr> <tr><td>3</td><td>Power supply V-</td></tr> <tr><td>4</td><td>B " RS-485 "</td></tr> <tr><td>5</td><td>A " RS-485 "</td></tr> <tr><td>6</td><td>Cable shield</td></tr> </table>	1	Power supply V+	2	SDI-12	3	Power supply V-	4	B " RS-485 "	5	A " RS-485 "	6	Cable shield							
1	Power supply V+																			
2	SDI-12																			
3	Power supply V-																			
4	B " RS-485 "																			
5	A " RS-485 "																			
6	Cable shield																			
	<p>Cable lenght 15 to 100 meters</p> <table border="1"> <tr> <td>Red</td> <td rowspan="2">Power supply V+</td> </tr> <tr> <td>Purple</td> </tr> <tr> <td>Yellow</td> <td rowspan="2">SDI-12</td> </tr> <tr> <td>Orange</td> </tr> <tr> <td>Green</td> <td rowspan="2">Power supply V-</td> </tr> <tr> <td>Pink</td> </tr> <tr> <td>2</td> <td>SDI-12</td> </tr> <tr> <td>3</td> <td>Power supply V-</td> </tr> <tr> <td>4</td> <td>B " RS-485 "</td> </tr> <tr> <td>5</td> <td>A " RS-485 "</td> </tr> <tr> <td>6</td> <td>Cable shield</td> </tr> </table>	Red	Power supply V+	Purple	Yellow	SDI-12	Orange	Green	Power supply V-	Pink	2	SDI-12	3	Power supply V-	4	B " RS-485 "	5	A " RS-485 "	6	Cable shield
Red	Power supply V+																			
Purple																				
Yellow	SDI-12																			
Orange																				
Green	Power supply V-																			
Pink																				
2	SDI-12																			
3	Power supply V-																			
4	B " RS-485 "																			
5	A " RS-485 "																			
6	Cable shield																			